K-LiTE Cylin

Compact and efficient ceiling mounted down lighters. High protection class & lumen output makes it versatile solution for both indoor & outdoor applications.

Product Description

- Luminaire made of pressure die cast aluminium, extruded aluminium & non corrosive stainless steel fasteners.
- · Polycarbonate optical lens.
- · Silicone gasket.
- · Cast aluminium plate for surface mounting onto the ceiling.
- Surface mounting on ceiling using hardware after connecting to the power supply.
- · Cable entries for through-wiring of mains supply cable.
- · Integral constant current power supply
- CRI (Ra): ≥80
- Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply.
- Ordering guide: KL-7576-CCT (Colour Temperature)
- · Available CCT: 2700K, 4000K (CW on request)



Product Benefits

- High luminous efficiency at reduced wattage.
- · Quick & simple installation.
- · Corrosion resistant and maintenance free.
- Sustainable LED technology offers durability and optimal light output with low power consumption.

Area of Application

Lobbies & Foyers, Retail outlets, Corridors, Corporate, Residential & Educational premises, Hospitality Industry, Commercial & Business Centers.

Available Finish

Pure polyester powder coated

- · Graphite grey
- · Anthracite grey
- Jet black



K-LiTE Cylin





Technical Specifications

General

ID : 7576 System Wattage 50W LED Driver Integral Constant Current Input Voltage : 230-240Vac Frequency : 50-60 Hz Operating Voltage : 100-300Vac Operating Temperature :-15°C~+50°C

Physical

Body : Extruded & die-cast aluminium

Diffuser : Polycarbonate Optical

Lens

Mounting : Surface - Ceiling Finish

: Graphite Grey Anthracite Grey Jet Black

Light Source

Light Source : NICHIA CŘI (Ra) :>80

LED Colour Temperature : 2700K, 4000K


(CW on request)

Driver

Power Supply : Integral Power Factor : ≥0.95 THD :<10% Surge Protection : 6KV Efficiency :>85%

Optical Performance

Beam Angle : 10°/ 28°/ 45°
























Cone Diagram







Note: It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at www.klite.in