K-LiTE Navi Spot

Surface mounted range of LED wall lights are a perfect fit for varied outdoor lighting applications. Designed to illuminate the wall and surface in front of wall and for light accents on vertical surfaces. Aesthetically designed sturdy construction ensures a long life against all weather condition, maintaining initial performances through the lifetime of the installation. Product offered in symmetrical light distribution.

Product Description

- Extruded aluminium hood cover integrated with die-cast module and extruded aluminium alloy (grade 6063) tube.
- · Heat resistant polycarbonate optical lens.
- · Stainless steel mounting clamp for easy installation onto the wall.
- Bracket to facilitate proper aiming of the luminaire at desired angle.
- · Available in 6° beam angle
- · Cable entries for through-wiring of mains supply cable.
- Integral constant current power supply
- CRI (Ra): >80
- Suitable for operation on 240V, 50Hz single phase ac supply.
- Ordering guide: KL-24334-CCT (Colour Temperature)
- · Available CCT: 2700K, 3000K, 4000K, 5700K











Product Benefits

- · High luminous efficiency at reduced wattage.
- · Elegant, Robust design
- · Sustainable LED technology offers durability and optimal light output with low power consumption.

Area of Application

Pathways in residential buildings & office complex, Sculptures, Passages, Structures and Security lighting.

Available Finish

Pure polyester powder coated RAL 9004 Black RAL 9007 Grey aluminium RAL 7016 Anthracite grey Graphite grey

Accessories

SPILL CONTROL SNOOT




Ø166 x 200

Push-on snoot for the lateral shielding of stray light. The cylindrical screen has a number of openings in it that allows water to flow out if it is fixed pointing upwards.



K-LiTE Navi Spot





Technical Specifications

General

ID : 24334 System Wattage : 30W LED Driver Integrated : Constant Current Operating Voltage : 100-300Vac Operating Temperature :-15°C~+50°C

Physical

Body : Die-Cast Aluminium with Extruded Aluminium Tube Diffuser : Polycarbonate Optical Lens Mounting : Surface - Wall

Finish : Powder coated RAL 9004 Black RAL 9007 Grey aluminium

RAL 7016 Anthracite grey Graphite grey

Light Source

Light Source : LUMILEDS CRI (Ra) :>80


LED Colour Temperature : 2700K / 3000K / 4000K

5700K


Driver


Power Supply : Integral : 230-240Vac Input Voltage Frequency : 50-60Hz Power Factor :>0.90 THD :<10% Surge Protection : 4KV Efficiency :>85% Dimmable Option : Analog / Dali

Optical Performance Beam Angle :6°










Note: It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at www.klite.in

K-LiTE Navi Spot





Technical Specifications

General

ID : 24335
System Wattage : 50W LED
Driver Integrated : Constant Current
Operating Voltage : 100-300Vac
Operating Temperature :-15°C∼+50°C

Physical

Body : Die-Cast Aluminium with Extruded Aluminium Tube
Diffuser : Polycarbonate Optical Lens
Mounting : Surface - Wall
Finish : Powder coated

RAL 9004 Black RAL 9007 Grey aluminium RAL 7016 Anthracite grey Graphite grey Light Source

Light Source : LUMILEDS
CRI (Ra) :>80
LED Colour Temperature : 2700K / 3000K / 4000K


5700K


Driver

Power Supply : Integral Input Voltage : 230-240Vac Frequency : 50-60Hz Power Factor :>0.90 THD :<10% Surge Protection : 6KV Efficiency :>85% Dimmable Option : Analog / Dali


Optical Performance


Beam Angle : 6°











Note: It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at www.klite.in